

Technical Data Sheet

CODE 11222

M 100/4" A LL

Wall/window axial fans



Certifications

CE CE

EAC EAC

G-Mark G-Mark


UKCA UKCA

CB TEST CERTIFICATE

TECHNICAL AND PERFORMANCE DATA

Frequency (Hz)	50	Ø Discharge hole (mm)	99
Inlet	Automatico	Voltage (V)	230-240
Insulation class	II°	Weight (Kg)	0,6
IP	X4	Max airflow (l/s)	25
Max absorbed current (A)	0,1	Max airflow (m ³ /h)	90
Max absorbed power (W)	18	Max pressure (mmH2O)	3
Max ambient temperature for continuous operation (°C)	50	Max pressure (Pa)	29
Nominal diameter (mm)	100	RPM	2300
		Sound pressure Lp [dB (A)] at 3 m	37,5

DIMENSIONS



Size A (mm)	159
Size B (mm)	160
Size C (mm)	100
Size D (mm)	47
Size E (mm)	Ø 99

PER INFORMAZIONI / FOR INFORMATION

ITALY

Pre Sales:
prevendita@vortice-italy.com
After Sales:
postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF

IRELAND
Sales Dept:
sales@vortice.ltd.uk
Technical Dept:
technical@vortice.ltd.uk

OTHER COUNTRIES

Sales Dept:
export@vortice-italy.com
After Sales:
after-sales@vortice-italy.com

Technical Data Sheet

CODE 11222

M 100/4" A LL

Wall/window axial fans




DESCRIPTION

- Material: UV resistant plastic (prevents ageing caused by exposure to sunlight).
- Nominal diameter 100 mm.
- Motor protected against thermal overload, with shaft turning in ball bearings (LL), coupled to screw type thermoplastic impeller with wing

- profile blades.
- Maximum air flow: 90 m³/h.
- Equipped with system by which the louvres of the grille are opened and closed automatically.

CURVES



ACCESSORIES



S 100/4

Code 22154



F 100/4"

Code 22131



KIT SCB (TRASF.E.C.)

Code 22481

PER INFORMAZIONI /
FOR INFORMATION

ITALY

Pre Sales:
prevendita@vortice-italy.com
After Sales:
postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF

IRELAND

Sales Dept:
sales@vortice.ltd.uk
Technical Dept:
technical@vortice.ltd.uk

OTHER COUNTRIES

Sales Dept:
export@vortice-italy.com
After Sales:
after-sales@vortice-italy.com