Technical Data Sheet CODE 11232 M 100/4" AT LL

Wall/window axial fans






Certifications		
CE	CE	
EAC	EAC	
(с G-М	ark	
UK U	КСА	
CB TEST CERTIFICATE		

TECHNICAL AND PERFORMANCE DATA

Frequency (Hz)	50	Ø Discharge
Inlet	Automatico	Voltage (V)
Insulation class	ll°	Weight (Kg)
IP	Х4	Max airflow
Max absorbed current (A)	0,1	Max airflow
Max absorbed power (W)	18	Max pressur
Max ambient temperature for	50	Max pressu
continuous operation (°C)		RPM
Nominal diameter (mm)	100	Sound press

Ø Discharge hole (mm)	99
Voltage (V)	230-240
Weight (Kg)	0,6
Max airflow (l/s)	25
Max airflow (m³/h)	90
Max pressure (mmH2O)	3
Max pressure (Pa)	29
RPM	2300
Sound pressure Lp [dB (A)] at 3 m	37,5

DIMENSIONS



Size A (mm)	159
Size B (mm)	160
Size C (mm)	100
Size D (mm)	47
Size E (mm)	Ø 99
	P -

PER INFORMAZIONI / FOR INFORMATION

ITALY Pre Sales: prevendita@vortice-italy.com After Sales: postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF IRELAND Sales Dept: sales@vortice.ltd.uk Technical Dept: technical@vortice.ltd.uk

ØЕ

OTHER COUNTRIES

Sales Dept: export@vortice-italy.com After Sales: after-sales@vortice-italy.com

Technical Data Sheet CODE 11232 M 100/4" AT LL

Wall/window axial fans

DESCRIPTION


• Material: UV resistant plastic (prevents ageing caused by exposure to sunlight).

• Nominal diameter 100 mm.

 Motor protected against thermal overload, with shaft turning in ball bearings (LL),coupled to screw type thermoplastic impeller with wing profile blades.

• Maximum air flow: 90 m3/h.

CURVES



ACCESSORIES





F 100/4" Code 22131

S 100/4 Code 22154

• Equipped with electronic timer designed to shut off the motor automatically after a set interval, selectable during installation in the range 3'-20' (default setting 3').

range 3'-20' (default setting 3'). • Equipped with system by which the louvres of the grille are opened and closed automatically.

PER INFORMAZIONI / FOR INFORMATION

ITALY Pre Sales: prevendita@vortice-italy.com After Sales: postvendita@vortice-italy.com UNITED KINGDOM & REP. OF IRELAND Sales Dept: sales@vortice.ltd.uk Technical Dept: technical@vortice.ltd.uk

OTHER COUNTRIES Sales Dept: export@vortice-italy.com After Sales: after-sales@vortice-italy.com

