# **Technical Data Sheet**

**CODE 11432** 

# M 150/6" AT LL

Wall/window axial fans





# Certifications

**CE** CE

FHI EAC

🕒 G-Mark

₽ nkca


CB TEST CERTIFICATE

### TECHNICAL AND PERFORMANCE DATA

Frequency (Hz)	50
Insulation class	II°
IP	X4
Max absorbed current (A)	0,15
Max absorbed power (W)	29
Max ambient temperature for continuous operation (°C)	50
Nominal diameter (mm)	160
Ø Discharge hole (mm)	156

Voltage (V)	220-240
Weight (Kg)	1,1
Max airflow (l/s)	93,1
Max airflow (m³/h)	335
Max pressure (mmH2O)	6
Max pressure (Pa)	59
RPM	2100
Sound pressure Lp [dB (A)] at 3 m	46

### **DIMENSIONS**



Size A (mm)	214
Size B (mm)	215
Size C (mm)	117
Size D (mm)	47
Size E (mm)	Ø
	156

## PER INFORMAZIONI / FOR INFORMATION

ITALY
Pre Sales:
prevendita@vortice-italy.com
After Sales:
postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF IRELAND
Sales Dept:
sales@vortice.ltd.uk
Technical Dept:
technical@vortice.ltd.uk

OTHER COUNTRIES
Sales Dept:
export@vortice-italy.com
After Sales:
after-sales@vortice-italy.com

### **Technical Data Sheet**

### **CODE 11432**

## M 150/6" AT LL

Wall/window axial fans




#### **DESCRIPTION**

- $\bullet$  Material: UV resistant plastic (prevents ageing caused by exposure to sunlight).
- Nominal diameter 150 mm.
- Motor protected against thermal overload, with shaft turning in ball bearings (LL), coupled to screw type thermoplastic impeller with wing profile blades.
- Maximum air flow: 335 m3/h.

- Equipped with electronic timer designed to shut off the motor automatically after a set interval, selectable during installation in the range 3'-20' (default setting 3').
- range 3'-20' (default setting 3').
   Equipped with system by which the louvres of the grille are opened and closed automatically.

#### **CURVES**



### **ACCESSORIES**





Code 22133



S 150/6

Code 22156

#### PER INFORMAZIONI / FOR INFORMATION

ITALY

Pre Sales:

prevendita@vortice-italy.com

After Sales:

 $postvendita@vortice\hbox{-}italy.com$ 

UNITED KINGDOM & REP. OF

**IRELAND** 

Sales Dept:

sales@vortice.ltd.uk

Technical Dept:

technical@vortice.ltd.uk

OTHER COUNTRIES

Sales Dept:

export@vortice-italy.com

After Sales:

after-sales@vortice-italy.com