




Technical parameters

Nominal data	
Voltage (nominal)	400 V
Frequency	50 Hz
Phases	3~
Input power	285 W
Input current	0.64 A
Impeller speed	1,397 rpm
Air flow	max 3,244 m ³ /h
Temperature of transported air	max 70 °C
Max temperature of transported air, when speed controlled	70 °C
Sound data	
Sound pressure level at 3m (20m ² Sabin)	48 dB(A)
Protection/Classification	
Enclosure class, motor	IP54
Insulation class	F
Data according to ErP	
ErP ready	ErP 2018
Dimensions and weights	
Duct dimension, inlet (height x width)	350 x 600 mm
Duct dimension, outlet (height x width)	350 x 600 mm
Weight	55.4 kg
Others	
Duct connection type	Rectangular
Motor type	AC


Dimension




	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
RSI 60-35	7	5	6	3	6	3	5	3	5	10	71	14	10	53	59
	0	0	4	9	2	7	9	4	5	8	7	0	0	2	7
	5	8	1	1	0	0	8	8							

Wiring


400V 3~



230V 3~



Performance curve



Hydraulic data										
Required air flow	1,622 m³/h									
Required static pressure	258 Pa									
Working air flow	1,622 m³/h									
Working static pressure	258 Pa									
Air density	1.204 kg/m³									
Power	258.3 W									
Fan control - RPM	1,407 rpm									
Current	0.60 A									
SFP	0.573 kW/m³/s									
Control voltage	400.0 V									
Supply voltage	400 V									
Sound power level		63	125	250	500	1k	2k	4k	8k	Total
Inlet	dB(A)	53	64	59	58	53	52	47	41	67
Outlet	dB(A)	56	69	67	68	68	66	59	50	75
Surrounding	dB(A)	30	51	49	46	48	43	39	31	55
Sound pressure level at 3m (20m² Sabine)	dB(A)	-	-	-	-	-	-	-	-	48
Sound pressure level at 3m free field	dB(A)	-	-	-	-	-	-	-	-	34
Accessories										

Accessories

GFL 60-35 Counter flange (2709)

Motor protect. switch S-DT 16E (161207)

RTRD 2 Speed Cont. Systemair (5941)

CO2RT-R-D Transmitter (6993)

HR1 Room Humidistat (215150)

RT 0-30 Room Thermostat (5151)

T 120 Timer (5165)

DXRE 60-35-3-2,5 Duct cooler (7956)

LDR 60-35 Silencer (5073)

RB 60-35/45-3 400V/3 Duct heat (9644)

VBR 60-35-2 Water heating batt (5467)

Motor protect. switch S-DT 16 (161206)

REV-5POL/07-7,5kW R/Y (33980)

RTRDU 2 Speed contr. Systemair (5945)

DTV500A (96807)

Presence detector/IR24-P (6995)

Safety switch 3-pole grey (210680)

DS 60-35 Flexible connection (1549)

FFK 60-35 Filter cassette rect (1761)

RB 60-35/27-2 400V/3 Duct heat (9643)

RBM 60-35/27 400V/3 Duct heate (5454)

VBR 60-35-4 Water heating batt (5475)

Documents

INSTALLATION_OPERATION_AND_MAINTENANCE_INSTRUCTION_KE_KT_RS_RSI_EN_002.PDF

COMMISSIONING_RECORD_FANS_EN.PDF