Technical Data Sheet CODE 11903 VORT NOTUS

De-centralised continuous axial fans






Certifications		
	Ce	CE
	())	ссс
	bre	SAP Q
	EHC	EAC
	UK CA	UKCA

TECHNICAL AND PERFORMANCE DATA

Frequency (Hz)	50
Insulation class	ll°
IP	Х4
Max absorbed current at Max speed (A)	0,025
Max absorbed current at Min speed (A)	0,018
Max absorbed power at Max speed (W)	2,8
Max ambient temperature for continuous operation (°C)	50
Nominal diameter (mm)	100
Power absorbed at 1st speed (W)	1,5
Voltage (V)	220-230

Weight (Kg)	0,8
Airflow at 1st speed (l/s)	3,3
Airflow at 1st speed (m³/h)	11,7
Max airflow at Max speed (l/s)	11,7
Max airflow at Max speed (m³/h)	42
Max pressure at Max speed (mmH20)	8,8
Max pressure at Max speed (Pa)	86,3
Pressure at 1st speed (mmH20)	2,4
Pressure at 1st speed (Pa)	23,5
Sound pressure at 3m at Max speed calculated in free field Lp [dB(A)]	17.3
Sound pressure at 3m at Min speed calculated in free field Lp [dB(A)]	10.1

DIMENSIONS



Size A (mm)	194,6
Size B (mm)	182
Size C (mm)	171
Size D (mm)	164
Size E (mm)	97,8
Size F (mm)	129
Size G (mm)	40,5
Size H (mm)	22,2
Size I (mm)	8

PER INFORMAZIONI / FOR INFORMATION

ITALY Pre Sales: prevendita@vortice-italy.com After Sales: postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF IRELAND Sales Dept: sales@vortice.ltd.uk Technical Dept: technical@vortice.ltd.uk

OTHER COUNTRIES Sales Dept: export@vortice-italy.com After Sales: after-sales@vortice-italy.com

Technical Data Sheet

CODE 11903

VORT NOTUS


De-centralised continuous axial fans

DESCRIPTION

• Material: UV resistant plastic (prevents ageing caused by exposure to sunlight).

Nominal diameter 100 mm
Three-phase EC brushless motor of external rotor type with shaft turning in ball bearings, designed to guarantee notably low energy

CURVES



PER INFORMAZIONI / FOR INFORMATION

ITALY Pre Sales: prevendita@vortice-italy.com After Sales: postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF

IRELAND Sales Dept: sales@vortice.ltd.uk Technical Dept: technical@vortice.ltd.uk

consumption and to provide 3 different air flow rates (the first two of which can be selected at the moment of installation) • Air flow between 11.7 m3/h and 42 m3/h

> OTHER COUNTRIES Sales Dept: export@vortice-italy.com After Sales: after-sales@vortice-italy.com

