Technical Data Sheet

CODE 11333

MEX 120/5" LL 1S

Wall axial fans





Certifications

CE CE

FH EAC

ے G-Mark

TK OKCA


CB TEST CERTIFICATE

TECHNICAL AND PERFORMANCE DATA

Frequency (Hz)	50
Insulation class	II°
IP	45
Max absorbed current at Max speed (A)	0,095
Max absorbed power at Max speed (W)	15
Max ambient temperature for continuous operation (°C)	50
Nominal diameter (mm)	120
Voltage (V)	220-240

Weight (Kg)	0,77
Max airflow at Max speed (l/s)	48,6
Max airflow at Max speed (m³/h)	175
Max pressure at Max speed (mmH20)	5
Max pressure at Max speed (Pa)	49,04
Max RPM	2075
Sound power at Min speed LWA [dB(A)]	52,8
Sound pressure at 3m at Max speed	32,3
calculated in free field Lp [dB(A)]	

DIMENSIONS



Size A (mm)	193
Size B (mm)	193
Size C (mm)	138
Size D (mm)	Ø 119
Size E (mm)	71
Size F (mm)	53
Size G (mm)	152
Size H (mm)	152
Size L (mm)	Ø 3,5

PER INFORMAZIONI / FOR INFORMATION

ITALY
Pre Sales:
prevendita@vortice-italy.com
After Sales:
postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF IRELAND
Sales Dept:
sales@vortice.ltd.uk
Technical Dept:
technical@vortice.ltd.uk

OTHER COUNTRIES
Sales Dept:
export@vortice-italy.com
After Sales:
after-sales@vortice-italy.com

Technical Data Sheet

CODE 11333

MEX 120/5" LL 1S

Wall axial fans



DESCRIPTION

- \bullet Housings made of shockproof and UV resistant white ABS.
- Nominal diameter 120 mm.
- AC motor equipped with long-life ball-bearings, mixed-flow impellers made of PP resistant to aggressive substances.
 Maximum air flow 175 m3/h.

- Integrated butterfly back-draught shutter designed to prevent unwanted air inflows when the appliance is switched-off.
- Protection rating IP45, suitable for installation in Zone 1 of bathrooms, as defined by international standard IEC 60364-7.

CURVES

PER INFORMAZIONI / FOR INFORMATION

UNITED KINGDOM & REP. OF ITALY IRELAND

Pre Sales: Sales Dept: prevendita@vortice-italy.com sales@vortice.ltd.uk

After Sales: Technical Dept: postvendita@vortice-italy.com technical@vortice.ltd.uk OTHER COUNTRIES

Sales Dept:

export@vortice-italy.com

After Sales:

after-sales@vortice-italy.com